

SPB ADHESIVE

ClassicBond Sprayable Bonding (SPB) Adhesive can dramatically reduce the overall time spent both on application & waiting for adhesive flash off, resulting in jobs coming in under time & less chance of the elements interfering as a result.

SPB Adhesive is a high-strength adhesive, specially formulated for gun application, formulated to bond ClassicBond membranes to a variety of substrates.

INTENDED USE

SPB Adhesive is designed as an alternative to brushable ClassicBond Bonding Adhesive. It will bond to a variety of substrates & provides excellent bond strength.

FEATURES & BENEFITS

- Gun applied high-strength adhesive that allows quick bonding. Cleaner, simpler application
- Up to 8 times faster application than traditional brush Bonding Adhesive
- Up to 4 times faster drying than traditional Bonding Adhesive
- Far greater operational window than traditional Bonding Adhesive
- More accurate application
- Zero wastage
- Up to 60m² per 14L per canister / 100m² 22L per canister

ASSEMBLY

1. Re move the black cap from the canister valve.
2. Attach the hose to the canister valve.
3. Attach the other end of the braided-hose to the spray-gun.
4. Using the locking-nut provided, attach the spray-tip to the end of the spray-gun.
5. Tighten all joints securely.
6. Fully open the valve on the canister.
7. Pull the trigger on the spray-gun to apply the adhesive.
8. Adjust the spray pattern by turning the black valve on the spray-gun anti-clockwise until you have a spray pattern approximately 300mm in width (Valve remains open during operational life).

APPLICATION*

1. Ensure all surfaces are clean, dry and free from contamination.
2. Open Pressure Adjustment Screw and hold gun 150-200mm from surface to be coated and squeeze the trigger. Apply an even coat of adhesive to both the membrane and roofing substrate.
3. Allow adhesive to flash off and become dry to the touch, allow a minimum of 4 minutes to maximum 30 minutes.
4. Bring the substrates into contact and consolidate the bond with a 50mm hand-roller.
5. When application is complete, close Pressure Adjustment Screw. Periodically the nozzle will require cleaning. Simply pressing nozzle into an area of dry adhesive will clear nozzle.

SRAYABLE BONDING ADHESIVE

PRECAUTIONS

1. SPB Adhesive is **EXTREMELY FLAMMABLE** - It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Store and use away from all sources of heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapours are heavier than air and may travel along ground to a distant ignition source and flash back.
2. Harmful by inhalation. Inhalation may cause nausea & vomiting. May cause dizziness & headache. Move exposed person to fresh air. Seek medical attention.
3. Harmful if swallowed. Ingestion may cause nausea & vomiting. Ingestion is irritating to the respiratory tract & may cause damage to the central nervous system. **DO NOT INDUCE VOMITING**. If swallowed, seek medical advice immediately & show container or label.
4. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of clean water for at least 15 minutes holding the eyelids open. Seek medical attention.
5. May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap & water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
6. Storage temperatures in excess of 25°C may affect product shelf life. Should the Bonding Adhesive be stored at temperatures below 15°C restore to room temperature prior to use.
7. Coverage rates are average and may vary due to conditions on site.
8. **KEEP OUT OF THE REACH OF CHILDREN.**

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The product labels
2. ClassicBond SPB Safety Data Sheet

PROPERTIES AND CHARACTERISTICS

- Appearance: Green
- Description: Aqueous Solution
- Temperature Resistance: -30°C - 85°C
- Application Temperature: 5°C - 30°C
- Storage: 5°C - 25°C
- Coverage: Up to 100m²
- Packaging: 14 litre / 22 litre canister
- Environmental: Solvent/Flammable/Hazardous
- Shelf Life: 1 year