



# ClassicBond® the original EPDM

## The Numbers Do Not Lie

- EPDM flat roof membranes have a life expectancy of at least 50 years.
- Half-century track record of performance and durability.
- Manufactured by worlds largest EPDM manufacturer

## Unrivalled

- Unmatched weatherability
- Flexibility
- Economical
- Safe – Heat free installation.
- Pressure-sensitive accessories available for virtually any penetration or detail.

## For You

- Wide variety of sheet widths – To suit each individual project and customer.
- Choice of Sheet thicknesses
- Seamless – Completely Reliable

ClassicBond Roofing Systems range of adhesives are specifically formulated and manufactured for the EPDM flat roofing industry. Roofs undergo huge variations in conditions and temperatures that standard, 'off the shelf' manufactured adhesives can't withstand for the long required life.

All our adhesives are heat and age tested to ensure their performance from day one.

### ClassicBond Deck Adhesive

This high strength low odour water based acrylic adhesive is specifically designed for use with ClassicBond EPDM roofing membrane to a range of deck surfaces.

#### Features

Available in 2.5l (7-10m<sup>2</sup> coverage), 5l (14-20m<sup>2</sup> coverage) and 15 Litre pails (42-60m<sup>2</sup> coverage).

Designed to be roller applied to flat roof surfaces.

For full usage details refer to ClassicBond Installation Manual.



### ClassicBond Bonding Adhesive

A high strength, solvent based bonding adhesive specifically designed and manufactured to withstand the temperature extremes of flat roofing installations. Perfect for bonding ClassicBond EPDM membrane to horizontal and vertical surfaces.

Suitable for a range of surfaces e.g. timber, brickwork, metal, PVC & concrete.

#### Features

Available in 2.5l (4-6m<sup>2</sup> coverage) and 5l (8-12m<sup>2</sup> coverage).

Application with a spreader, brush or medium pile roller.

For full usage details refer to ClassicBond Installation Manual.



### ClassicBond EPDM Primer

ClassicBond EPDM Primer is a solvent based product designed for one step cleaning and priming of EPDM and other suitable surfaces prior to the application of ClassicBond Pressure Sensitive (PS) EPDM accessories.

ClassicBond Primer must be used when any of the following ClassicBond products are installed:

- 75mm PS Seam Tape
- 150mm PS Cover Strip
- 225mm Uncured Flashing
- PS Pipe Seals
- PS Walkway Pads.

#### Features

Available in 0.5l, 1l and 3.8 litre containers.

For application details refer to ClassicBond Installation Manual.



# ClassicBond® the original EPDM

## ClassicBond Water Cut-Off Mastic

For use as a compression termination, this one part self wetting mastic is used in a variety of situations where a compression termination of the ClassicBond EPDM membrane is required.

### Features

Each tube covers 3 linear metres.

This is only to be used as a compression type mastic, not as a sealant for wall chases or gaps.

For full usage details refer to the ClassicBond Installation Manual.



## ClassicBond Lap Sealant

The ClassicBond lap sealant mastic cures of to give a rubber consistency. This allows the mastic bead to expand and contract with the environment. Ideal for sealing wall chase details and using as a finishing bead to compression type joints.

### Features

Each tube produces up to 6 linear metres of mastic bead.

For full usage details refer to the ClassicBond Installation Manual.



## ClassicBond Weathered Membrane Cleaner

Used as a cleaner for aged EPDM that has been exposed to weather and environmental conditions. An excellent cleaner to remove dirt and contaminants from the EPDM membrane or from other single ply membranes leaving them in a suitable condition for the application of ClassicBond Primer and PS tapes for the repair or renovation of existing flat roof membranes.

### Features

Fast, easy cleaning of old membrane

Available in 1 litre bottle or 18 litre can

